

One component economic cementation putty polymer modified for concrete & masonry.

DEFINITION

Novo Fair Putty 100 B is one component economic cementation putty polymer modified for concrete & masonry based on cement, modified polymer and selective additives.

ADVANTAGES

1. Good resistance for water & weather.
2. Give a smooth finish to walls.
3. It is easily sanded to give the perfect finish required for high quality tabs.
4. Can be used as an under layer for all types of paints.

FIELDS OF USE

1. Used for smoothing cement or lime based on plasters, paper or whenever a super smooth surface is required.
2. Also, for concrete walls before applying all types of paints.
3. For filling small holes producing any cracks.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION VALUE

DISCRIPTION	VALUE
Color	White, gray
Density	(1.50 ±0.05) gm. / Cm ³
Coverage	1.5- 2 kg / m ² (depending on surface conditions)
Shelf life	12 months (under suitable storage conditions)

PACKING

- Plastic Sack 25 kg

SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo Latex Sealer** if required or mouser the surface.
3. Add (9-10) liter/ 25 kg - of water clean pail then add (powder) step by step with continuous stirring by suitable mixer (small quantity can be mixed by hand). mixing well until obtain good homogenous putty without any lumps
4. Let mixed putty for 3 minutes the mix again for 2 minutes to be ready for application
5. Applied by knife putty, only one coat is sufficient for a smooth surface. For a rough surface, two or more coats are required. Max. thickness should be less than 1mm for one coat
6. Each coat must be dried and sanded down with sand paper before applying a further coat.
7. Clean used tools by water immediately after finish.

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight.

PRECAUTIONS & SAFETY

- **Novo Fair Putty 100 B** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

NOVOCHEM S.AE

المقر الرئيس والمصنع


مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem

