

Two component cementation putty polymers modified for concrete & masonry.

DEFINITION

Novo Fair Top is two components cementation putty polymer modified for concrete & masonry based on cement, modified polymer and selective additives.

ADVANTAGES

1. Good resistance for water & weather.
2. Give a smooth finish to walls.
3. It is easily sanded to give the perfect finish required for high quality tabs.
4. Can be used as an under layer for all types of paints.

FIELDS OF USE

1. Used for smoothing cement or lime based on plasters, paper or whenever a super smooth surface is required.
2. Also, for concrete walls before applying all types of paints.
3. For filling small holes producing any cracks.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
<i>Color</i>	White, gray
<i>Density</i>	(1.80 ±0.05) gm. / cm ³
<i>PH</i>	8-9
<i>Coverage</i>	1.5- 2 kg / m ² (depending on surface conditions)
<i>Shelf life</i>	12 months (under suitable storage conditions)

NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

www.novochem.net

info@novochem.net

[@](#) [f](#) Novochem



SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo Latex Sealer** if required or mouser the surface.
3. Add liquid component **(A)** (liquid) to clean pail then add component **(B)** (powder) step by step with continuous stirring by suitable mixer (small quantity can be mixed by hand). mixing well until obtain good homogenous putty without any lumps – Can added water not more than 15 % if required.
4. Let mixed putty for 3 minutes the mix again for 2 minutes to be ready for application
5. Applied by knife putty, only one coat is sufficient for a smooth surface. For a rough surface, two or more coats are required. Max. thickness should be less than 1mm for one coat
6. Each coat must be dried and sanded down with sand paper before applying a further coat.
7. Clean used tools by water immediately after finish

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight.

PACKING

Group 30 kg

Plastic sack: 25 kg

Plastic pail: 5kg

Or customer requires group weight.

PRECAUTIONS & SAFETY

- **Novo Fair Top** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.