

Interior plastic matt paint. complies to Egyptian Standard NO. 1539\2008

DEFINITION

Novo GO is a high-quality water-based matt emulsion paint formulated with acrylic co-polymer to give it an exceptional flat smooth finish for interior use.

Novo Go complies to Egyptian Standard NO. 1539\2008

ADVANTAGES

1. Economic and easy apply.
2. Good abrasion resistance.
3. Adheres well and can be applied on all surfaces of building.
4. White and colored to suit all tastes.
5. Used as a very good undercoat.

FIELDS OF USE

1. Use for cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.
2. Suitable for homes, schools, hospitals, office building, hotels etc.
3. Used as an undercoat before applying top emulsion coat

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
Color	White and colored
Glossy	Matt
Density	(1.66 ±0.05) kg / L
PH	8- 9
Coverage	9–11 m ² /L /coat (depending on surface conditions)
Shelf life	12 months (under suitable storage conditions)

SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo Sealer** if required.
3. Apply one or more coat Novo putty to smoothing the surface.
4. Cavities can be filled with **Novo Ready**

DIRECTIONS OF USE

Mixing before use

Novo GO should be mixed well before using to obtain homogenous liquid.

Applications

- Apply one or more coats of **Novo GO** by suitable roller, brush or spray.
- **Novo GO** can be diluted with clean water 1 - 5 % if required to facilitate the application.

Guide coating system for Interior system.

Primer Sealer	Novo Sealer	1 Coat
Putty	Novo Ready	2 Coats
Under Coat	Novo GO	1 Coat
Finish Coat	Novo GO	1 Coat

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight. (10-30) C°

PACKING

Plastic pail: 8 lit

PRECAUTIONS & SAFETY

- **Novo GO** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem

