

Novo Go Sealer

Last update: - 24 / 06 / 2021 (2)

Emulsion Sealer primer.

DEFINITION

Novo Go Sealer is an emulsion Sealer primer based on special emulsion polymer for interior and exterior use

ADVANTAGES

- Ready to use and easy to apply with its enhanced properties
- 2. give a smooth finish to walls before putty application
- Can be used as an under layer for all types of paints and wall papers.

FIELDS OF USE

- As a primer sealer with superior sealing properties.
- Most suitable for internal and external use on cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE	
Color	Milky white	
Glossy	Matt	
Density	$(1.20 \pm 0.05) \text{ kg / L}$	
Viscosity	15 – 20 Poise	
PH	8-9	
Coverage	$5-7 \text{ m}^2/\text{ kg}$ (depending on	
	surface conditions)	
Shelf life	12 months (under suitable	
	storage conditions)	

SURFACE PREPARATION

- 1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
- 2. Mix the product well before application
- 3. Apply one coat or more by brush, roller or spray

Guide coating system for Interior and Exterior

Primer Sealer	Novo Go Sealer	1 Coat
Putty	Novo Go Putty	2 Coats

STORAGE CONDITIONS

Storage conditions are to keep containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed. (10 -30) Co

PACKING

• Plastic Pail 9 Litres (As customer require)

PRECAUTIONS & SAFETY

- Novo Go Sealer is non flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر — الجيزة — مدينة السادس من أكتوبر — المنطقة الصناعية الثالثة — بلوك 91،102،103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel.: (+202) 369 182 33 Fax: (+202) 369 182 32















