

Good Quality Three Components Epoxy Adhesive Putty.

DEFINITION

Novo Putty EP is good quality three components epoxy putty based on solvent free epoxy resin, suitable hardeners and selected fillers.

ADVANTAGES

- 1. Easy to apply.
- 2. Smooth adhesive putty.
- 3. Good repairing and filling for cracks.
- 4. Good bonding adhesive
- 5. Good mechanical strength.
- 6. Good anchorage of blots, etc.

FIELDS OF USE

- Also be used for filling small holes PACKING 1. producing any cracks.
- 2. Smoothing and repairing the surfaces of concrete wall and pipes.

PROPERTIES @ 25 C°

White, grey, and many colors
100 %
4 A: 1 B: 5 C
1. $85 \pm 0.05 \text{ g/cm}^3$
30 – 45 MIN
(15 – 35) C°.
24 hrs.
7 days
12 months in suitable storage conditions
(Depending on surface conditions)

DIRECTIONS OF USE

- 1. Clean surfaces or cracks of dust, oils and grease.
- 2. Use suitable drilling mixer (max. 300 rpm) to Mix comp A well with comp B then add comp C step by step to obtain suitable homogenous consistency.

(Depending on required application)

- 3. Apply the product by suitable steel putty knife.
- 4. Remove any excess of product by using suitable sponge with Novo SOL T 09.

Group (5 kg)

HEALTH AND SAFETY

- Wear protective clothes, gloves, glasses and face protection.
- Good ventilations in case of spraying application.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.
- For eye contact, rinse with plenty clean water then ask for medical advice

NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر – الجيزة – مدينة السادس من أكتوبر – المنطقة الصناعية الثالثة – بلوك 91،102،103

Headquarters and Factory Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel.: (+202) 369 182 33 Fax: (+202) 369 182 32 www.novochem.net info@novochem.net

🞯 🗗 Novochem



World Of Chemistry

FP-14-07/EN

ISSUE DATE/REV: - 1/5/2021

ISSUE REV NO: - 2/1