

**Interior plastic matt paint.** complies to Egyptian Standard NO. 1539\2008

## DEFINITION

**Novo king** is a water-based matt emulsion paint formulated with acrylic co-polymer to give it an exceptional flat smooth finish for interior use.

**Novo king** complies to Egyptian Standard NO. 1539\2008

## ADVANTAGES

1. Economic and easy apply.
2. Good abrasion resistance.
3. Adheres well and can be applied on all surfaces of building.
4. White and colored to suit all tastes.
5. Used as a very good undercoat.

## FIELDS OF USE

1. Use for cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.
2. Suitable for homes, schools, hospitals, office building, hotels etc.
3. Used as an undercoat before applying top emulsion coat

## PHYSICAL PROPERTIES @ 25 C°

| DISCRIPTION       | VALUE  |
|-------------------|--|
| <i>Color</i>      | White and colored  |
| <i>Glossy</i>     | Matt   |
| <i>Density</i>    | (1.66 ±0.05) kg / L  |
| <i>PH</i>         | 8- 9   |
| <i>Coverage</i>   | 9–11 m <sup>2</sup> /L /coat (depending on surface conditions) |
| <i>Shelf life</i> | 12 months (under suitable storage conditions)                  |

## SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo Sealer** if required.
3. Apply one or more coat Novo putty to smoothing the surface.
4. Cavities can be filled with **Novo Ready**

## DIRECTIONS OF USE

### Mixing before use

**Novo king** should be mixed well before using to obtain homogenous liquid.

### Applications

- Apply one or more coats of **Novo king** by suitable roller, brush or spray.
- **Novo king** can be diluted with clean water 1 - 5 % if required to facilitate the application.

### Guide coating system for Interior system.

|                      |               |         |
|----------------------|---------------|---------|
| <b>Primer Sealer</b> | Novo Sealer   | 1 Coat  |
| <b>Putty</b>         | Novo go putty | 2 Coats |
| <b>Under Coat</b>    | Novo king     | 1 Coat  |
| <b>Finish Coat</b>   | Novo king     | 1 Coat  |

## STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight. (10-30) C°

## PACKING

Plastic pail: 8 lit

## PRECAUTIONS & SAFETY

- **Novo king** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

### NOVOCHEM S.AE

المقر الرئيس والمصنع

91,102,103 بلوك - المنطقة الصناعية الثالثة - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6<sup>th</sup> of October City - 3<sup>rd</sup> Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

[www.novochem.net](http://www.novochem.net)

[info@novochem.net](mailto:info@novochem.net)

Novochem

